



Compact Network Management



K4Edge Server – Fit Edition

A cloud managed edge platform providing advanced SDWAN, Security, QoS, and LAN services

- Manages WAN sources and user data for optimal connectivity and controlled access
- Cloud Managed, powerful user interface with Real-Time Metering and Analytics
- Combine and control WAN sources with Advanced Routing and Bandwidth Bonding
- Protect and Secure Network Integrity with Deep Packet Inspection (DPI), Traffic Policies, and VPN
- Compact, Fanless

Industrial Design

- Small form factor (4.4" x 3.4" x 1.4")
- Hardened design, fanless, aluminum case
- Expandable ports
- 2x USB3
- 2x USB2
- GE compatible USB
- 5G modem over USB

K4 Edge Applications

- Intuitive System Management locally or from the Cloud
- **Cloud Service Portal** for fleet management
- **Mobile App** management

Advanced QoS

- Deep Packet Inspection with Application, Domain, and IP filtering
- Rate, Quota, Priority management
- One-click client/group mgmt
- Priority / Shaping / Blocking

Security and performance

- Optimized Cellular/VSAT management via Cloud
- **K4 Mobility Management**
- Integrated stateful firewall
- DPI + CF to secure the Internet

Local Area Network Management


- Connected and Routed Networks
- LAN, DHCP, DNS, Bonjour/M-DNS
- App, Device, and Group QoS

Software Defined Wide Area Network – SDWAN

- WAN Link Priority and Bonding
- Lossless Advance Bonding
- USA Internet
- VPN Services

Operations

- **K4 Connect** provides remote management to Edge networks
- Role-based access with SSO
- Cloud managed - using K4's Service Portal and Mobile App



Specifications

Quickly add K4Edge as a Service (KaaS) to any network installation



K4Edge Fit – Back View



K4Edge Fit – Front View

WAN Management	Supports up to 5x WAN sources
Ethernet	2x GE ports, additional 4x GE ports using USB expansion
Network Configurability	Up to 500 Clients, 30 VLAN Networks; Stateful Firewall
Compute Power	Intel x86 Atom or Celeron class processor ; 8 GB RAM, 128 GB
Expansion	2x USB 3.0 ports - 5G modem adapter supported
Cooling	Passive, Fanless - Silent
Mounting	Standalone / Universal / DIN mount kit available
Power	+12VDC (30W Max); 100-240 VAC, 50-60 Hz (AC/DC Power Supply Included)
Physical	4.4" x 3.4" x 1.4" / 111 x 85 x 35 mm - 2.25 lbs / 1 kg
Environmental	Operating temp: -10 to +50 C; Humidity up to 95%, non-condensing
Warranty	1 year limited